

EB-3362-I

Features

- Vortex86DX3 1GHz SoC
- Onboard 2GB DDR3
- SATA and SD support
- Giga LAN support
- +8 to +24VDC Input
- Operating in -20°C to +70°C
- VESA mount support
- Auto Power On support
- EtherCAT Support



Specifications

Part Number	EB-3362-L2851C3P-I	EB-3362-C2G2SIM-I	EB-3362-L2C2851G1E-I	
CPU	DM&P Vortex86DX3 - 1GHz			
RAM	DDR3 2GB RAM onboard			
BIOS	AMI BIOS			
Display	VGA, resolution support up to 1920 x 1080			
LAN	10/100Mbps LAN x1 10/100/1000Mbps LANx1	10/100Mbps LAN x1	10/100Mbps LAN x1 10/100/1000Mbps LANx1	
USB	External x3 Internal x1 (for wireless dongle)	External x3	External x3 Internal x1 (for wireless dongle)	
SD Slot	1	1	---	
Mini PCIe	1	1	---	
SIM Card Slot	---	1	---	
SATA	---	1	1	
RS232	3	2	2	
RS485	1	---	1	
GPIO	---	8-bit GPIO x2	8-bit GPIO x1	
Dimension	115 x 115 x 35mm			
Power Requirement	+8 to +24VDC			
Weight	510g			
Operating Temperature	-20°C - +70°C			
Auto Power On	Support			
VESA Mounting	100 x 100mm			
O/S Support	Windows 7 Windows XP Professional POS Ready (WePOS)	Windows Embedded Standard 7 Windows Embedded 2009 QNX	Windows Embedded Compact 7 Linux VxWorks	Windows Embedded CE6.0 DOS Free BSD

