


# APL-NUC-N3350



## Specifications

CPU	Intel® Apollo Lake N3350 2.40GHz (Burst) 1.10GHz Dual Core		
RAM	DDR3L 1866MHz memory support up to 8GB in SO-DIMM slot x1		
BIOS	AMI BIOS		
Expansion	MiniPCIe (half-size) x1		
Display	Intel® HD Graphics with MultiDisplay support HDMI : Maximum resolution support up to 3840 x 2160 @ 30Hz VGA: Maximum resolution support up to 1920 x 1200 @ 60Hz		
Audio	Realtek ALC662VD		
LAN	Realtek 8111H GigaLAN x2		
Disk Support	mSATA x1	SATA device x1	
I/O Interface	COM x1 SMBus x1	USB (ver. 3.0) x4 8-bit GPIO x1	USB (ver. 2.0) x2 SIM Card holder x1
Connectors	4-pin wafer for SATA power output x1 9-pin D-sub connector for COM x1 15-pin D-sub connector for VGA x1 MiniPCIe slot for mSATA x1 Phone Jack for Line-out/MIC-in x1	5-pin header for SMBUS x1 9-pin header for USB2.0 x1 MiniPCIe slot x1 RJ45 connector for GigaLAN x2 SIM card holder x1	7-pin SATA connector for SATA x1 10-pin header for 8-bit GPIO x1 HDMI connector x2 Power Jack for 12VDC input x1 USB connector for USB3.0 x4
Power Requirement	12VDC standard input from power jack or internal 2-pin power connector support for ATX/AT mode		
Operating Temperature	0°C to 50°C		
Dimension	158 x 164 mm		
O/S Support	Windows 10	Linux	

## PRELIMINARY VERSION