




Features

- Intel® Alder Lake-P MCP Processors, 15W
- 21.5" 1920x1080 LCD Panel
- Full Flat Res. or P-Cap Touch
- Fanless Solution
- IP66 Front Panel Mount Housing
- Wide Range DC Input
- Up to 3 Extended Displays
- Optional WLAN with External Antenna
- CE, FCC, VCCI Class B Passed
- Adjust Brightness Function

Specification

Product	WLP-7H20-22 MBKFT		WLP-7H20-22 MBKPT	
Main System	CPU	Intel® 12th Gen Alder Lake-P MCP Processors, 15W		
	Graphic	Intel® Gen 12 Graphics		
	Memory	Dual Channel DDR4 3200 MHz ,2 x 260 SO-DIMM, up to 64GB (32GB per DIMM)		
	TPM	TPM2.0		
	OS Support	Optional Windows 10 (2019-LTSC) (64bit), Windows 11 (64bit)		
Display	Size	21.5" 16:9		
	Resolution (pixel)	1920 x 1080 (Full HD)		
	Number of Colors	16.7M colors		
	View Angle (H/V)	170(H) / 160(V)		
	Brightness(cd/m ² , nit)	250 nits		
	Contrast Ratio	1000:1 (Typ)		
Touch Panel	Type	Full flat resistive touch panel	Full flat projected capacitive touch panel	
	Light Transmission	80 ± 5%	>=86%	
	Hardness	>=3H	>=7H	
	Lifetime	35M times	100M times	
Storage & Expansion	Storage	1 x 2.5" SATA HDD drive bay (with anti-vibration mechanism) 1 x M.2 (KEY M, 2242/2260/2280) with PCIe Gen4 x4 for SSD		
	Expansion	1 x M.2 (Key B, 3042/3052) with PCIe x1, USB3.2, USB2.0 and SIM for 4G/5G 1x SIM socket connected to M.2 key B 1 x M.2 (Key E, 2230) with PCIe, USB2.0 and CNVi for Wireless		
I/O Ports	USB	2 x USB 2.0, 2 x USB 3.2 Gen2, 2 x USB 3.2 Gen2 Type-C (Support DP1.4a display output, power output 5V/3A)		
	COM	2 x RS-232/422/485(COM1, COM2), 1 x RS-232(COM3)		
	LAN	2 x RJ-45 2.5 Gbps		
	HDMI	2 x HDMI 2.0b		
	Audio	2 x 3.5mm phone jack connector (Line-out, Mic-in)		
	Control Keys	Rear bottom: Power on /off		
Power	Power input	DC12~28V input		
	Power adapter	External, 100 watts, universal 100 ~240V AC in, 19V DC out, 5.26A (PSU with PSE)		
Environmental	Temperature	Operating Temperature: 19V DC Input 0~50°C (IEC60068-2-56, air flow cooling) 19V DC Input 0~40°C (IEC60068-2-2, natural cooling) Storage Temperature: -20~60°C		
	Humidity	Operating & Storage: 10 ~ 90%, non-condensing		
	IP / IK Level	IP66 at front, IK05		
Mechanical Characteristics	Housing	Front bezel is Aluminum, others are SECC with black coating		
	Dimensions (Net: mm)	TBD		
	Weights (Net: kg))	TBD kg		
	Mounting	Panel mount / VESA (75x75)		
Certification	FCC-B, CE (EMC), VCCI, ICES-003			



Major Options	
Options	<ol style="list-style-type: none"> 1. Wireless and BT kit (2 ant) 2. 2.5" SSD 3. Stainless steel front bezel 4. Silver front bezel 5. 1 x USB 2.0 (By Cable) 6. Windows 10 (2019-LTSC) (64bit), Windows 11 (64bit) 7. M.2 NVMe SSD 8. 2 x 2.5" SSD for RAID 0,1 9. Chassis type housing
Customization	<ol style="list-style-type: none"> 1. Open frame housing 2. Sunlight Readable by 1000 nits LCD + Optical Bonding (Impact protection level: IK08) 3. Storage door Solution 4. 5G Module 5. WDT AP/API 6. Intel i3-1215UE / i7-1265UE, DC

Order Information

Item	Touch	Description
WLP-7H20-22 (MBKFT)	Full Flat Resistive Touch	22" i5-1245UE 3.3GHz,4GRAM,500G HDD Panel mount
WLP-7H20-22 (MBKPT)	Full Flat Pcap Touch	22" i5-1245UE 3.3GHz,4GRAM,500G HDD Panel mount

I.O.(STD)



- | | |
|----------------------|--------------------|
| 1 1 x DC-in | 6 2 x USB 3.2 Gen2 |
| 2 2 x RS-232/422/485 | 7 2 x LAN |
| 3 1 x RS-232 | 8 2 x USB 2.0 |
| 4 2 x USB Type-C | 9 Line-out |
| 5 2 x HDMI | 10 Microphone-in |
| | 11 Power on/off |

