



SHARK Bezel-free Fanless Panel PC

SHARK 7"

SHARK 10.1"



The back panel I/O is flexible for customized configuration.



Model Name		7" + 2I268C	10.1" + 2I268C
Dimension (mm)		184.7W x 40H x 122.5D mm	250W x 40H x 168D mm
Weight		2 Kg	2.3 Kg
Hard drive		N/A	2.5" HDD
LCD brand		CPT	CPT
LCD size		7 inch, 16:9	10.1 inch, 16:9
Max Resolution		WSVGA 1024 x 600	1280 x 800
Luminance (cd/m ²)		375	500
Contrast Ratio		400:1	500:1
Viewing Angle (H-V)		140(H)-110(V)	140(H)-120(V)
Backlight		LED	LED
Touch Screen		Resistive touch screen	Resistive touch screen
MB		2I268C-DVI	2I268C-DVI
CPU		Intel Cedarview-M N2600/N2800 1.6/1.86 GHz	Intel Cedarview-M N2600/N2800 1.6/1.86 GHz
Chipset		Intel Cedarview-M + NM 10	Intel Cedarview-M + NM 10
Memory	Type / Capacity	DDR3 800 MT/s for N2600, Max up to 2GB DDR3 1066 MT/s for N2800, Max up to 4GB	DDR3 800 MT/s for N2600, Max up to 2GB DDR3 1066 MT/s for N2800, Max up to 4GB
	SO-DIMM	N/A	N/A
	On board memory	2GB	2GB
SSD Storage	CF (CFast)	N/A	N/A
	mSATA	Yes (Half Size)	Yes (Half Size)
	On Board SSD	Optional	Optional
VGA		Optional	YES
DVI / HDMI		DVI	DVI
USB		2	Built-in 2 x USB, expand up to 5 x USB
COM		Optional	Built-in 1 x COM, expand up to 2 x COM
MiniPCle		2	2
SIM Card Holder		Optional	Optional
GPIO		4DI / 4DO (Optional)	4DI / 4DO (Optional)
Ethernet		Realtek GbE x 1	Realtek GbE x 1
Audio		Line-out	Line-out
Power Input		DC IN +12V	DC IN +12V
Battery		option (3500 mAh)	option (3500~10500mAh)
Mounting		VESA 75	VESA 75
Panel frame water proof		IP65	IP65
Optional MB		2I268HB	2I268HB
Expansion		GPS, 3G/4G, Bluetooth, WI-FI, I/O	GPS, 3G/4G, Bluetooth, WI-FI, I/O
Operating Temp.		-20°C~-60°C for mSATA	-20°C~-60°C for mSATA
Operating Humidity		5~90% @ 39°C, non-condensing	5~90% @ 39°C, non-condensing