R15IM3S-EHC3

15" ARM A53 E Series HMI Panel PC



KEY FEATURES

- 15" 1024 x 768 Resolution with Projected Capacitive Multi-Touch (P-CAP)
- ARM A53 Quad Core 2.0GHz CPU
- Fanless cooling system and ultra-low power consumption
- Front IP65 Water and Dust Proof
- Android 11
- Support Android or Linux operating system



SPECIFICATIONS

Display			
Resolution	1024x768	Size	15.0 inches
Contrast Ratio	2000:1	Panel Brightness	300.0 nits
View Angles	88,88,88,88	Active Area	304.1x228.1 mm
Touch / Glass	Projected Capacitive Multi Touch Screen		
System Specification			
WLAN	Support (Optional)	ВТ	Support (Optional)
Processor	ARM A53 (Quad Core 2.0GHz)	Memory	4GB LPDDR4
Storage	eMMC: Onboard 32 GB	Operating System	Android 11 (Upgradeable to Android 13) Linux Yocto 5.10.104 with QT 5.15 (Optional) Linux Ubuntu (Optional)
Mechanical			
Dimension	367 x 291 x 65.8 mm	Weight	3.0 kg
Mounting	Panel Mount VESA Mount	Enclosure	Metal Front Bezel with Plastic Back Cover
Cooling System	Fanless Design	Cut out	342x261mm
Environment			
Operating Humidity	10% to 90% RH, Non-Condensing	Operating Temperature	0°C to 50°C
Storage Temperature	-20°C to 60°C	Shock	MIL-STD-810G Method 516.6 Procedure I
Vibration	MIL-STD-810G Method 514.6 Procedure I	IP rating	Front IP65
Certification			
Certification	CE, FCC		
IO Ports			
		0 : 10 (
USB Port	2 x USB 2.0 Type A 1 x Micro USB 2.0 OTG	Serial Port	1 x RS232/422/485 (Default RS232)
USB Port SD Card Slot	2 x USB 2.0 Type A 1 x Micro USB 2.0 OTG 1 x Micro SD card slot (Max to 32GB)	Video	1 x RS232/422/485 (Default RS232) 1 x Micro HDMI Output (Optional)
	1 x Micro USB 2.0 OTG		
SD Card Slot	1 x Micro USB 2.0 OTG 1 x Micro SD card slot (Max to 32GB) 1 x LAN 10/100/1000 Mbps		


Power Cord VESA screws Manual Mounting clips

Power

Power Rating 12V DC with Terminal Block Adapter 12V 50W

DIMENSIONS

UNIT:MM



NOTE

- 1. This is a simplified drawing and some components are not marked in detail.
- 2. The product shown in this datasheet is a standard model. For diagrams that contain customized or optional I/O, please contact the Winmate Sales Team for more information.
- 3. All specifications are subject to change without prior notice.