


W22ITWS-MHB1-EX

21.5" Intel® Core™ i5-1135G7 C1D2 HMI Panel PC



KEY FEATURES

- Intel® 11th Generation Tiger Lake UP3 Core™ i5 CPU, HMI Panel PC
- Signature true flat display screen with edge-to-edge design
- Aluminum, anti-corrosion treated housing
- Superior sealing with front IP65 protection against dust and water
- Projected Capacitive Multi-Touch Screen (PCAP)
- Fanless Design, C1D2 HMI Panel PC
- Support wide range 9-29 V DC input
- Quick & Easy Removable 2.5" SSD Bay Slot
- Support PCIe x4 Card
- Class 1 Division 2, Group A-D, T4 Certification




SPECIFICATIONS

Display				
Resolution	1920x1080	Size	21.5 inches	
Contrast Ratio	1000:1	Panel Brightness	350 nits	
View Angles	89,89,89,89	Active Area	476.64x268.11 mm	
Touch / Glass	Projected Capacitive Multi Touch Screen			
System Specification				
WLAN	Support (Optional)	BT	Support (Optional)	
Expansion Port	Modular Design for easy service in the field		Processor	Intel® Tiger Lake Core™ i5-1135G7, 2.4 GHz (turbo up to 4.2GHz)
Memory	2 x SODIMM, DDR4 3200 MHz, 4GB 8GB (Optional) 16GB (Optional) 32GB (Optional)		Storage	1 x M.2 2280 NVMe SSD, 128GB up to 512GB 1 x 2.5" Removable 256GB SSD up to 512GB (Optional)
Ethernet controller	Intel® Ethernet Controller I211-AT + Intel® Ethernet Connection I219-LM		Operating System	Windows 10 IoT Enterprise (Optional)
Mechanical				
Dimension	532.6 x 324.1 x 94.2 mm		Mounting	Panel mount VESA Mount
Enclosure	Metal Housing		Cooling System	Fanless design
Cut out	504x304mm			
Environment				
Operating Humidity	10% to 90% (non-condensing)		Operating Temperature	-20~60°C
Storage Temperature	-40~80°C		Shock	MIL-STD-810G Method 516.6 (Optional)
Vibration	MIL-STD-810G Method 514.6		Altitude	nan
Certification				
Certification	CE, FCC Hazardous Location Safety: Class 1, Division 2, Group A, B, C, D			

IO Ports			
Power Input	1 x 9~29V DC, 3-Pin Terminal Block	USB Port	4 x USB 3.2 Gen.1 (Type-A)
Serial Port	2 x RS232/422/485 (Default RS232) 1 x RS232	Video	1 x DP1.4 1 x HDMI 2.0 (Optional)
Audio	1 x Audio Combo Connector (Mic in / Line Out)	Expansion Port	1 x mPCIe slot 1 x PCIe x16 slot (x4 signal)(module max size:180x121mm) 1 x M.2 2230 Key E slot for WiFi 1 x M.2 2280 Key M slot for NVMe SSD Swappable 2.5" HDD/SSD Bay Slot
LAN	2 x Giga LAN RJ45 Connector	Indicator	1 x LED Indicator for storage
Control			
Button	1 x Power Button with LED Indicator 1 x Reset Button		
Accessory			
Accessory	100~240V AC to DC Adapter Power Cord Open Wire Cable with terminal block connector Driver CD & Manual Mounting clips VESAs screws		
Power			
Power Rating	9V~29V DC with protection fuse	Adapter	12V 120W

DIMENSIONS UNIT:MM

Winmate W22ITWS-MHB1-EX



NOTE

1. This is a simplified drawing and some components are not marked in detail.
2. The product shown in this datasheet is a standard model. For diagrams that contain customized or optional I/O, please contact the Winmate Sales Team for more information.
3. All specifications are subject to change without prior notice.