

Z81

2MP Outdoor Zoom Dome with D/N, Adaptive IR, Extreme WDR, SLLS, 4.4x Zoom Lens




- 2 Megapixel
- Day & Night with Superior Low Light Sensitivity and Adaptive IR LED
- 4.4x Zoom Lens with f2.7 mm~12 mm / F1.4 with Auto Focus
- Extreme WDR (120 dB)
- 30 fps at 1920 x 1080
- Wide Angle
- Weatherproof (IP67)
- Built-in Analytics

PHOTO INDICATION




- 1 DC12V Power Input Jack
- 2 Ethernet Port
- 3 Reset Button
- 4 Memory Card Slot

DIMENSION DIAGRAM



ACCESSORY OPTIONS

Power Supply	
PPOE-0001	 IEEE 802.3af PoE Injector for Class 1, 2 or 3 devices, with universal adapter

Popular Mounting Solutions	
Surface	Accessories not required

* For more mounting solutions, please refer to www.acti.com/mountingselector

PRODUCT SPECIFICATION

• Device

Device Type	Outdoor Zoom Dome
Image Sensor	Progressive Scan CMOS
Sensor Size	1/2.9"
Day / Night	Yes
Low Light Sensitivity	Superior
Minimum Illumination	Color: 0.1 lux at F1.8 B/W: 0 lux (IR LED on)
Color to B/W Switch	ISP based switch, configurable
Mechanical IR Cut Filter	Yes
IR Sensitivity Range	700~1100nm
IR LED	Adaptive IR LED x 30
IR Working Distance	30 m (0 lux, 30 IRE, Gain 255, Auto shutter mode)
Electronic Shutter	1/6" ~ 1/100000" (manual and auto mode)
S/N Ratio	> 52 dB

• Lens

Focal Length / Aperture	Zoom Lens, f2.7 mm ~ f12 mm / F1.4
Focus	Auto Focus
Horizontal Viewing Angle	102° ~ 32°
Viewing Angle Adjustment	Pan: 0 ~ 360° Tilt: 15° ~ 90° Rotate: 0° ~ 360°

• Video

Compression	H.265, H.264, MJPEG
Max. Frame Rate vs. Resolution	30 fps at 1920 x 1080 30 fps at 1280 x 720 30 fps at 720 x 576 30 fps at 704 x 288 30 fps at 640 x 360 30 fps at 352 x 288
Multi-Streaming	Simultaneous Triple Streams based on 3 Configurations
Image Enhancement	Extreme WDR (120 dB) White Balance (Auto, Outdoor, Fine Tune, Sodium Lamp, Locked) Brightness Saturation Contrast, Sharpness (Auto) Automatic Gain Control 2D+3D Digital Noise Reduction Defogging
Privacy Mask	8 Configurable Regions
Text Overlay	User Defined Text on Video
Built-in Analytics	Tampering
Image Orientation	Image Flip, Mirror and Rotation

• Audio

Audio Type	1-way, Built-in Microphone
------------	----------------------------

• Network

Protocol & Service	L2TP, IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SIP, 802.1x
Ethernet Port	1, Ethernet (10/100 Base-T), RJ-45 connector
Security	IP Address Filtering, HTTPS Encryption, Password Protected User Level, IEEE 802.1X Network Access Control

• Alarm

Alarm Trigger	Video Motion Detection (2 regions) Notify Control Center
Alarm Response	E-mail Notification with Snapshots Upload Video or Snapshot to FTP server

• Interface

Local Storage	MicroSDHC memory card slot (card not included)
---------------	--

• General

Power Source	PoE, DC 12V (adapter not included)
Weight	0.45 kg (0.99lb)
Dimensions (Ø x H)	129 x 110 mm (5.08" x 4.3")
Environmental Casing	Weatherproof (IP67 rated)
Mount Type	Surface, Pendant
Operating Temperature	-40°C ~ 60°C (-40°F ~ 140°F)
Relative Humidity	≤ 95% RH
Approvals	CE (EN 55022 CLASS A, EN 55024) FCC (Part15 Subpart B Class A) IP67

• Integration

Unified Solution	Fully compatible with ACTi software
ISV Integration	Software Development Kit (SDK) available ONVIF compliant (Profile S)
Firmware Access Browser	Microsoft Internet Explorer 8 ~ 11 Safari with QuickTime (partial functionality) Other Browsers with VLC (partial functionality)
Auto Firmware Upgrade	No
GPS Position	No